

ツイスターリング（固定・往復運動用取付寸法表C）

8. ツイスターリングの固定・往復運動用取付寸法表C

運動用シール（Vmax = 30m/分）の場合の推奨寸法

（単位：mm）

内径シール					
呼び番号	ロッド C	みぞの内径 D + 0.2	みぞ幅 F + 0.1	ツイスターリング の内径 ID	
T-001	0.8	2.4	1.2	0.74	
T-002	1.0	3.0	1.4	1.06	
T-003	1.5	4.1	1.7	1.42	
T-003 ½	1.8	3.4	1.2	1.78	
T-004	1.8	4.9	2.0	1.78	
T-005A	2.0	4.6	1.7	2.00	
T-005	2.5	5.6	2.0	2.57	
T-006	3.0	6.1		2.90	
T-007	3.5	6.6		3.68	
T-008A	4.0	7.1		4.00	
T-008	4.5	7.6		4.47	
T-009	5.0	8.1		5.28	
T-010	6.0	9.1		6.07	
T-011	7.5	10.6		7.65	
T-012A	8.0	11.1		8.20	
T-012	9.0	12.1		9.25	
T-110	9.0	13.7		3.0	9.20
T-111A	10.0	14.7			10.20
T-111	11.0	15.7	10.77		
T-112	12.0	16.7	12.37		
T-113	14.0	18.7	13.95		
T-114B	15.0	19.4	14.80		
T-114	15.5	20.2	15.55		
T-115A	16.0	20.7	16.20		
T-115	17.0	21.7	17.12		
T-116	18.5	23.2	18.72		
T-210A	18.0	24.5	4.0		18.20
T-210	19.0	25.5			18.66
T-211	20.0	26.5		20.22	
T-212	22.0	28.5		21.82	
T-213	23.0	29.5		23.40	
T-214	25.0	31.5		25.00	
T-215	27.0	33.5		26.58	
T-216	28.0	34.5		28.17	
T-217	30.0	36.5		29.75	
T-218	31.0	37.5		31.35	
T-219	33.0	39.5		32.92	
T-220	35.0	41.5		34.52	
T-221	36.0	42.5	36.09		
T-222	38.0	44.5	37.70		
T-325	38.0	47.9	6.0	37.46	
T-326A	39.0	48.9		39.20	
T-326	40.0	49.9		40.64	
T-327	44.0	53.9		43.80	
T-328A	45.0	54.9		45.20	
T-328	47.0	56.9		47.00	
T-329A	49.0	58.9		49.20	
T-329	50.0	59.9		50.16	
T-330	53.0	62.9		53.35	
T-331	56.0	65.9		56.50	
T-332	60.0	69.9		59.70	
T-333	63.0	72.9		62.86	
T-334	66.0	75.9	66.05		
T-335	69.0	78.9	69.20		

外径シール					
呼び番号	ツイスターリング の外径 OD	みぞ幅 F + 0.2	みぞの外径 B - 0.1	シリング内径 A	
T-001	2.78	1.2	0.9	2.5	
T-002	3.56	1.4	1.5	3.5	
T-003	4.46	1.7	1.9	4.5	
T-003 ½	3.82	1.2	2.4	4.0	
T-004	5.34	2.0	2.4	5.5	
T-005A	5.00	1.7	2.4	5.0	
T-005	6.13	2.0	2.9	6.0	
T-006	6.46		3.4	6.5	
T-007	7.24		3.9	7.0	
T-008A	7.56		4.4	7.5	
T-008	8.03		4.9	8.0	
T-009	8.84		5.9	9.0	
T-010	9.63		6.4	9.5	
T-011	11.21		7.9	11.0	
T-012A	11.76		8.9	12.0	
T-012	12.81		9.9	13.0	
T-110	14.44		3.0	9.8	14.5
T-111A	15.45			10.8	15.5
T-111	16.01	11.3		16.0	
T-112	17.61	13.3		18.0	
T-113	19.19	14.3		19.0	
T-114B	19.72	15.6		20.0	
T-114	20.79	16.3		21.0	
T-115A	21.24	17.3		22.0	
T-115	22.36	17.8		22.5	
T-116	23.96	19.3		24.0	
T-210A	25.26	4.0		18.5	25.0
T-210	25.72			19.5	26.0
T-211	27.28		20.5	27.0	
T-212	28.88		22.5	29.0	
T-213	30.46		23.5	30.0	
T-214	32.06		25.5	32.0	
T-215	33.64		27.5	34.0	
T-216	35.23		28.5	35.0	
T-217	36.81		30.5	37.0	
T-218	38.41		31.5	38.0	
T-219	39.98		33.5	40.0	
T-220	41.58		35.5	42.0	
T-221	43.15	36.5	43.0		
T-222	44.76	38.5	45.0		
T-325	48.12	6.0	38.1	48.0	
T-326A	49.86		40.1	50.0	
T-326	51.30		42.1	52.0	
T-327	54.46		45.1	55.0	
T-328A	55.86		46.1	56.0	
T-328	57.66		48.1	58.0	
T-329A	59.86		50.1	60.0	
T-329	60.82		51.1	61.0	
T-330	64.01		54.1	64.0	
T-331	67.16		57.1	67.0	
T-332	70.36		60.1	70.0	
T-333	73.52		64.1	74.0	
T-334	76.71	67.1	77.0		
T-335	79.86	70.1	80.0		

ツイスターリング (固定・往復運動用取付寸法表C)

運動用シール (Vmax = 30m/分) の場合の推奨寸法

(単位: mm)

内径シール				
呼び番号	ロッド C	みぞの内径 D + 0.2	みぞ幅 F + 0.1	ツイスターリング の内径 ID
T-336	72.0	81.9	6.0	72.40
T-337	75.0	84.9		75.56
T-338	79.0	88.9		78.75
T-339A	80.0	89.9		80.50
T-339	82.0	91.9		81.90
T-340	85.0	94.9		85.10
T-341	88.0	97.9		88.26
T-342	92.0	101.9		91.45
T-343	95.0	104.9		94.60
T-344	98.0	107.9		97.80
T-345	100.0	109.9		100.96
T-346	104.0	113.9		104.15
T-347	107.0	116.9		107.30
T-348	110.0	119.9		110.50
T-349	114.0	123.9		113.66
T-425	114.0	127.0		8.0
T-426	117.0	130.0	116.85	
T-427	120.0	133.0	120.00	
T-428	123.0	136.0	123.20	
T-429	125.0	138.0	126.36	
T-430	130.0	143.0	129.55	
T-431	132.0	145.0	132.70	
T-432	136.0	149.0	135.90	
T-433	139.0	152.0	139.06	
T-434A	140.0	153.0	140.50	
T-434	142.0	155.0	142.25	
T-435	145.0	158.0	145.40	
T-436	148.0	161.0	148.60	
T-437	152.0	165.0	151.76	
T-438	158.0	171.0	158.10	
T-439A	160.0	173.0	160.50	
T-439	165.0	178.0	164.46	
T-440	170.0	183.0	170.81	
T-441	177.0	190.0	177.16	
T-442A	180.0	193.0	180.50	
T-442	183.0	196.0	183.50	
T-443	190.0	203.0	189.86	
T-444	196.0	209.0	196.20	
T-445	200.0	213.0	202.56	
T-446	215.0	228.0	215.30	
T-447	230.0	243.0	228.00	
T-448A	235.0	248.0	235.50	
T-448	240.0	253.0	240.70	
T-449	253.0	266.0	253.40	
T-450	266.0	279.0	266.10	
T-451	280.0	293.0	278.80	
T-452	292.0	305.0	291.50	
T-453	304.0	317.0	304.20	
T-454	317.0	330.0	316.90	
T-455	330.0	343.0	329.60	
T-456	342.0	355.0	342.30	
T-457	355.0	368.0	355.00	
T-458	368.0	381.0	367.70	
T-459	380.0	393.0	380.40	
T-460	390.0	403.0	393.10	

外径シール				
呼び番号	ツイスターリング の外径 OD	みぞ幅 F + 0.2	みぞの外径 B - 0.1	シリンダ内径 A
T-336	83.06	6.0	73.1	83.0
T-337	86.22		76.1	86.0
T-338	89.41		80.1	90.0
T-339A	91.16		82.1	92.0
T-339	92.56		83.1	93.0
T-340	95.76		86.1	96.0
T-341	98.92		90.1	100.0
T-342	102.11		92.1	102.0
T-343	105.26		96.1	106.0
T-344	108.46		100.1	110.0
T-345	111.62		102.1	112.0
T-346	114.81		105.1	115.0
T-347	117.96		110.1	120.0
T-348	121.16		112.1	122.0
T-349	124.32		115.1	125.0
T-425	127.66		8.0	117.0
T-426	130.85	119.0		132.0
T-427	134.00	122.0		135.0
T-428	137.20	127.0		140.0
T-429	140.36	129.0		142.0
T-430	143.55	132.0		145.0
T-431	146.70	135.0		148.0
T-432	149.90	137.0		150.0
T-433	153.06	141.0		154.0
T-434A	154.50	142.0		155.0
T-434	156.25	145.0		158.0
T-435	159.40	147.0		160.0
T-436	162.60	150.0		163.0
T-437	165.76	153.0		166.0
T-438	172.10	160.0		173.0
T-439A	174.50	162.0		175.0
T-439	178.46	167.0		180.0
T-440	184.81	172.0		185.0
T-441	191.16	179.0		192.0
T-442A	194.50	182.0		195.0
T-442	197.50	187.0		200.0
T-443	203.86	192.0		205.0
T-444	210.20	197.0		210.0
T-445	216.56	207.0		220.0
T-446	229.30	217.0		230.0
T-447	242.00	229.0		242.0
T-448A	249.50	237.0		250.0
T-448	254.70	242.0		255.0
T-449	267.40	257.0		270.0
T-450	280.10	267.0		280.0
T-451	292.80	282.0		295.0
T-452	305.50	293.0		306.0
T-453	318.20	307.0		320.0
T-454	330.90	317.0		330.0
T-455	343.60	332.0	345.0	
T-456	356.30	347.0	360.0	
T-457	369.00	357.0	370.0	
T-458	381.70	372.0	385.0	
T-459	394.40	387.0	400.0	
T-460	407.10	397.0	410.0	